

CCD-IS88A/50MN



Features:

- 1/3" SONY low illumination CCD
- Resolution: 540TVL
- Built-in multi-language OSD menu
- 4privacy zones adjustable
- Motion detect and mirror function
- Electronic shutter adjustable
- IR: $\Phi 48$, IR distance: 40~50m
- Zoom outside adjustable
- IP66, cable inside bracket,lighting-proof function

Specifications:

MODEL	CCD-IS88A/50MN
Pick-up device	1/3" SONY low illumination CCD
Effective pixels	PAL:500*582
Resolution	540TVL
Sensor size	4.9mm*3.7mm
Sync system	Internal
Min. illumination	0lux(IR on)
S/N ratio	More than 48dB
Electronic shutter	FLK/Manual/Fixed
Lens	Standard configuration 9-22mm manual lens (4-9mm Korea manual lens,4-9mm Korea ICR lens, 9-22mm Korea ICR lens optional)
Angle of View	40.6°-16.2°
Flickerless mode	On/off
Mirror function	On/off
Privacy zone	On/off (4 AREAS)
BLC	On/off (64 AREAS)

Motion detect	On/off (64 AREAS)
Gamma	Auto/manual
White balance	Auto(ATW, AWB, FIXED, MANUAL)
AGC	On/off(0-255)
Video output	1.0V p-p Composite Video Output, 75 Ohm
Day&Night	Color 、 B/W 、 Auto (level adjust)
IR distance	40~50m
Power supply	DC12V
Power consumption	200mA/500mA(IR on)
Operating temp	-10°C ~ 50°C

Dimension:

