

## SDM-SDZ100/O



### Features:

- 10X optical zoom, 10X digital zoom
- 0.05°/sec Pan/Tilt speed available
- Max 360°/sec high speed Pan/Tilt motion
- IR CUT Day/Night function
- OSD menu to set speed dome functions
- Provide keyboard shortcuts operation
- Privacy zone function
- Compact and mini structure

### Specifications:

MODEL	SDM-SDZ100/O
CCD	1/4" Interline Transfer CCD
Max. Pixels	795(H)×596(V) 470K PAL
Effective Pixels	752(H)×582(V) 440K PAL
Horizontal Res.	500 TVL(Color),570 TVL(B/W)
S/N Ratio	50dB(AGC Off)
Zoom	10X optical zoom, 10X digital zoom
Focal Length	F1.8, f=3.8~38mm
Min. Illumination	0.7Lux (Color), 0.02Lux (B/W), 50 IRE
Day & Night	Auto / Day / Night (ICR)
Focus	Auto / Manual / Semi-Auo
Iris	Auto / Manual
Shutter Speed	128X~1/120000 sec
AGC	Normal / High / Off
White Balance	Auto / Manual / (Red, Blue Gain Adjustable)

BLC	Low / Middle / High / Off
Flickerless	Selectable
SSNR	Low / Middle / High / Off
Pan / Tilt Range	Pan: 360°(Endless), Tilt: 180°(Auto Flip), 95°(Normal)
Pan / Tilt Speed	Preset: 360°/sec, Swing: 1~180°/sec Manual: 0.05~360°/sec(Proportional to zoom)
Preset	127 Preset ( Lable, Camera Image Setting )
Pattern	4 Patterns, 1200 commands ( About 5 minutes)/ Pattern
Swing	8 Swing
Group	8 Groups ( 20 actions entities per group )
Other Functions	Auto flip, Auto parking, Power up action etc
Communication	RS-485
Protocol	Pelco-D, Pelco-P selectable
Privacy Zone	4 zones
OSD	Menu / PTZ information etc
IP66 for outdoor use	Yes
Rated Power	MV-X10t-D: DC12V / 0.8A, MV-X10t-A: AC24V / 0.4A
Dimention	Dome: $\phi$ 115, Housing: $\phi$ 147.51×41(H)mm
Weight	About 1 Kg
Operating Temp	-20°C~50°C